

MXI-4E SERIES



PXI BUS EXPANDERS

- Supports remote control of PXI and CompactPCI chassis
- PCIe - PXI Implementation
- Transparent PCI / PCIe bridge operation
- 2.5 Gb/s maximum data rate
- 1, 3 or 7 m copper cabling with rugged, captive screw connectors



DESCRIPTION

The MXI-4E PXI Bus Expander allows for direct control of PXI systems from a PCI or PCIe slot in a desktop computer or server. MXI-4E interface cards can also be used for linking multiple PXI chassis. MXI-4E technology utilizes a high-bandwidth link that is transparent to software applications and drivers, therefore providing the ability to use high performance desktop computers or servers to control PXI systems.

FEATURES

Since PXI is based on the industry-standard PCI bus, the MXI-4E Bus Expander provides a transparent link where all PXI modules appear to the user as if they were PCI boards within the computer itself. However, with PXI technology, users benefit from an increased number of slots, power and cooling per slot, module selection, and synchronization features.

The MXI-4E employs MXI-Express technology and builds on the standard PCI-to-PCI bridge architecture by splitting the bridge into two halves which are connected by a high speed serial link. The MXI-4E kit consists of a PCI card, a copper cable, and a PXI interface card. Individual kit components may be purchased separately for spares or to meet your specific requirements. The MXI-Express kits provide control of PXI chassis via a PCIe card.

MULTI-CHASSIS SYSTEMS

The MXI-4E Bus Expander can be used to connect multiple PXI chassis in a star or daisy-chain configuration within a single system. To connect two PXI chassis together, install a MXI-4E-PXI peripheral slot controller card into any peripheral slot of the master chassis, and then connect the appropriate cable to a MXI-4E-PXI remote controller in slot 1 of the slave chassis.

APPLICATIONS

- Remote control of a PXI or cPCI chassis via desktop PC
- Remote control of a PXI or cPCI chassis via a PXI chassis with an embedded controller

MXI-4E SERIES



SPECIFICATIONS

POWER REQUIREMENTS	
MXI-PCle-X1-A	+3.3 V: 210 mA (max)
MXI-PXI-X1-A	+3.3 V: 720 mA (max)
GENERAL	
Maximum Cable Length	7 M (copper) 200 M (fiber)
Operating Temperature	0 °C to +50 °C
Storage Temperature	-20 °C to +80 °C
Operating Relative Humidity	10 to 90%, non-condensing
Storage Relative Humidity	10% to 90%, non-condensing
Dimensions MXI-PCle-X1-A	2.48" x 4.76" (6.3 cm x 12.1 cm)
Weight	MXI-PCle-X1-A: 0.11 lb (typ) MXI-PXI-X1-A: 0.31 lb (typ)
Safety	IEC 61010-1, EN 61010-1 UL 61010-1, CSA 61010-1
EMC	EN 61326-1 (IEC 61326-1): Class A emissions; Basic immunity EN 55011 (CISPR 11): Group 1, Class A emissions
Compatibility	PXI Hardware Specification 2.1, PCI Specification 3.0

Note: Specifications are subject to change without notice

ORDERING INFORMATION

MXI-CBL-PCle-X1-1M-AD	PCle -to-PXI 1 M cable
MXI-CBL-PCle-X1-3M-AD	PCle -to-PXI 3 M cable
MXI-CBL-PCle-X1-7M-AD	PCle -to-PXI 7 M cable
ACCESSORY	
MXI-CBL-PCle-X1-1M-AD	MXI-E x1 Copper Cable 1M
MXI-CBL-PCle-X1-3M-AD	MXI-E x1 Copper Cable 3M
MXI-CBL-PCle-X1-7M-AD	MXI-E x1 Copper Cable 7M

Note: The MXI-4E Series is supplied by a 3rd party and resold by Marvin Test Solutions.