

# GX5296



## DYNAMIC DIGITAL I/O WITH PER CHANNEL TIMING, PROGRAMMABLE LOGIC LEVELS AND PMU PXI CARD

- Timing per pin, multiple time sets and flexible sequencer
- 32 Input / Output channels with PMU per pin
- 125 MHz vector rate
- 64 M Vectors per channel (64 Mb per channel vector memory)
- Per channel drive / sense voltage range of -2 V to +7 V
- 4 Additional control / timing channels with programmable levels & PMU



## DESCRIPTION

The GX5296 offers advanced dynamic digital I/O performance and capabilities in a single slot, 3U PXI format. The 32-channel, GX5296 features timing per pin, multiple time sets, data formatting, and an advanced sequencer – providing users with the capability to emulate and test complex digital busses for system, board or device test applications. Offering sub-nanosecond edge placement resolution per pin and a PMU per pin, the GX5296 has the ability to perform both DC and AC parametric testing. Each digital channel can be individually programmed for a drive hi, drive lo, sense hi, sense lo, and load value (with commutation voltage level). In addition, each channel offers a parametric measurement unit (PMU) providing users with the capability to perform parallel DC measurements on the DUT (device under test).

The GX5296 supports deep pattern memory by offering 64 Mb per pin of vector memory with dynamic per pin direction control and with test rates up to 125 MHz. The board supports both Stimulus / Response and Real-time Compare modes of operation, allowing the user to maximize test throughput for go / no-go testing of components and UUTs that require deep memory test patterns. The single board design supports both master and slave functionality without the use of add-on modules.

## FEATURES

The GX5296's timing generator supports 8 timing phases and 4 windows for drive and sense timing respectively. Each phase and window is comprised of two timing edges - assert / de-assert and an open window / close window respectively. Timing resolution of 250 ps is supported for each of these edges. The 8 phases and 4 windows are available for mapping edge timing to a specific channel.

Up to 64 unique time set values can be defined for each phase / window and are selectable on a per sequence step basis. Additionally, six data formats are supported - NR (no return), R0, R1, RHIZ, and RC (Return to Complement), RSC (Return Surround with Complement). Data formatting is assigned on a per channel basis.

Pin electronic resources are independent on a per channel basis and include a full-featured PMU for DC characterization of DUTs. The PMU can operate in the force voltage / measure current or force current / measure voltage mode. Additionally, 4 additional pin electronics resources are available for use as timing and/or control resources – providing programmable drive and sense levels from -2 to +7 volts.

The GX5296 employs a PLL based, clock system which offers programmable vector clock rates up to 125 MHz. In addition, a clocks per pattern (CPP) divider (1 to 256) is available, providing additional clocking and edge placement flexibility. External input and output synchronization signals are also supported, providing the ability to synchronize the GX5296 to external events or time bases.

The GX5296 offers a full-featured sequencer. Capabilities include conditional jump, unconditional jump, subroutine jump, or looping. Additionally, the sequencer has the ability to handshake with external signals in order to synchronize with a UUT. Handshaking settings can be selected on a per step basis and include Handshake Pause and Resume resources. Total sequencer memory size is 4096 steps with each step capable of accessing 1 to 64 M of vector memory.



# GX5296



## SOFTWARE

The GX5296 is supplied with graphical vector development / waveform display tools (GtDIO6xEasy) as well as a virtual instrument panel, 32 / 64-bit DLL driver libraries, and documentation. The virtual panel can be used to interactively control and monitor the instrument from a window that displays the instrument's current settings and status. In addition, **ICEasy** Test Suite is available, which provides a comprehensive set of software tools - facilitating the development and debugging of test programs for semiconductor devices. The suite includes I-V curve and Shmoo plot tools for analyzing a device's DC and AC characteristics, a library of device test development tools for creating test programs and characterizing devices, file import tools for importing and converting STIL, WGL, VDC/EVCD, and ATP digital file formats as well as GtDIO6xEasy. The complete suite of tools interfaces seamlessly with Marvin Test Solutions' ATEasy, a test executive and test development environment.

## APPLICATIONS

- Semiconductor test
- ASICs testing
- A/D and D/A testing
- Video acquisition / playback applications
- High speed, bi-directional bus testing / emulation



# GX5296



## SPECIFICATIONS

CHANNEL I/O SPECIFICATIONS	
Number of Data I/O Channels	32 per card
Channel Direction Control	Input or Output per vector, per channel
Drive and Sense Programmable Voltage References	32 Drive Hi / Drive Lo 32 Sense Hi / Sense Lo
Drive Voltage Level	Level: Drive Hi: -2 V to +7 V, Drive Lo: -2 V to +7 V
	Accuracy: $\pm 20$ mV (max)
	Resolution: 16 bits, 250 $\mu$ V
	Leakage Current $\pm 15$ nA (max)
Output Impedance	50 $\Omega$ (typ)
Drive Current	$\pm 35$ mA (max)
Rise / Fall Times	0.5 ns typical for a 2 V pulse
Channel Skew	160 ps, typical between the same card 320 ps max, after calibration, for all channels within a domain (Drive and sense)
Sense Voltage	Range: Sense Hi: -1.75 V to +7 V, Sense Lo: -1.75 V to +7 V
	Threshold Accuracy: $\pm 25$ mV
	Resolution: 16 bits, 250 $\mu$ V
Input Leakage Current	$\pm 15$ nA (max)
Minimum Data Sense Pulse Width	4ns
Voltage Termination (VTT)	Range: -2 V to +7 V
	Accuracy: $\pm 20$ mV
	Resolution: 16 bits, 250 $\mu$ V
Pull-Up / Pull-Down Current Source / Sink	Range: +24 mA to -20 mA, programmable on a per channel basis
	Accuracy: $\pm 124$ $\mu$ A
	Resolution: 16 bits
Voltage Commutation (Vcomm)	Range: -2V to +7V, programmable on a per channel basis Note: VTT and Vcomm share a common voltage source, only one mode supported per channel.
	Accuracy: $\pm 20$ mV (typ)
	Resolution: 16 bits, 250 $\mu$ V
Vector Memory	64 Mb per channel

Data Output Formats (Assigned per channel)	Drive Hi, Drive Lo, Hi-Z Formatted Data: No return, Return to 1, Return to 0, Return to Hi-Z, Return to complement, Surround by complement
Drive Data Timing (Assigned per channel)	Data assert / de-assert based on Phases 0-7
Capture Mode Timing (Assigned per channel)	Windows 0 -3 Mask Capture on open edge of Window Capture on closing edge of Window

### TEST MODES

Drive / Sense Modes	Output: Drive Hi, Drive Lo, Hi-Z Sense: Sense Lo, Sense Hi Drive / Expect: -DriveHi Expect Lo -Drive Lo Expect Hi -Drive Hi Expect Hi -Drive Lo Expect Lo Expect valid level Expect invalid level Repeat previous opcode Invert previous opcode
Record Modes	Real Time Compare: -Record errors for inputs with Good 1 & Good 0 -Record errors for inputs with only a Good 1 -Pass/ fail condition based on expect / actual data compare Record Data: -Record raw data based on NOT a Good 0 -Record raw data based on a Good 1 -Record raw data, Good 1 & Good 0
Error Memory	Record data and address for compare errors 1K deep error memory

### TIMING

Master Clock (T0) Frequency Range	1 MHz (min); 125 MHz (max)
T0 Clock Period Programming Resolution	250 ps
Accuracy	$\pm 0.02\%$ of programmed value + accuracy of reference clock (PXI 10 MHz or external reference clock)
Jitter	50 ps RMS, typical
Reference	PXI 10 MHz clock or XClk (external clock) input

# GX5296



Clocks per Vector Range	Programmable per sequence step, 1 to 256 T0 clock period must be > 50 ns if programming per seq step
Phase and Window Timing	8 phases, 4 windows, user assigned to DIO channels
Timing Set Sequence Control	64 Timing Sets supporting 8 Phases, 4 Windows, and 4 K sequence steps.
Phase and Window Timing Resolution	250 ps
Minimum Phase / Window Pulse Width; Assert / Return Or Open / Close	4 ns
Phase / Window Reference	Phase: System (T0) or Pattern Clock (selectable per Seq Step) Window: Pattern clock only
<b>STATUS AND CONTROL SIGNALS</b>	
Input Trigger Functions	Pause - Resume (2), Halt, Run
Trigger Source	PXI Triggers 0-7 Trigger is edge or level programmable
Sync / Clock Output Functions	Sync (2), Sequence Active, Seq Flag , Failed Vector, Valid Pass, T0 Clk, Vector Clock, Seq Clock, PXI 10 MHz, , Record Active, Counter Active , GoSub Active, Subroutine Rtn, Return Flag, Last Vector, Channel Compare
Sync / Clock Outputs	Timing / Sync / Trigger Connector (J3) - (4) Aux pin electronic channels (bidirectional); supported functions: Sequence Active, T0 Clk, Vector Clock, Seq Clock, PXI 10 MHz, Failed Vector, Sequence Active, Counter Active, Last Vector, GoSub Active - PXI Triggers 0-7; supported functions: Seq Flag, Sync (2), Channel Compare, Sequence Active, Failed Vector, Valid Pass
<b>SEQUENCER</b>	
Commands	Jump, Conditional Jump, Loop, Call Subroutine, Return, Pause, Halt
Loop Counters	Single loop counter Loop count range: 1 – 64K or continuous
Sequencer Memory	4096 Steps

Phase Trigger	T0_CLK (System Clock) or PAT_CLK (Vector clock)
Window Trigger	PAT_CLK (Vector clock)
Patterns per Sequence Step	1 to 64M
Sequence Loop	1 to 1M, continuous
Jump	Conditional / Unconditional
Jump Conditions	Error True, Sequence Timeout True, Signal Level (High / Low), Signal Edge (Rising / Falling)
<b>AUXILIARY I/O CHANNELS</b>	
Number Channels	4, can be used for timing / control functions or for static I/O
Drive Voltage Level	Level: Drive Hi: -2 V to +7 V, Drive Lo: -2 V to +7 V
	Accuracy: $\pm 20$ mV (max)
	Resolution: 16 bits, 250 $\mu$ V
	Leakage Current $\pm 15$ nA (max)
Output Impedance	50 $\Omega$ (typ)
Drive Current	$\pm 35$ mA (max)
Rise / Fall Times	0.5 ns typical for a 2 V pulse
Sense Voltage	Range: Sense Hi: -1.75 V to +7 V, Sense Lo: -1.75 V to +7 V
	Threshold Accuracy: $\pm 25$ mV
	Resolution: 16 bits, 250 $\mu$ V
Input Leakage Current	$\pm 15$ nA (max)
Voltage Termination (VTT)	Range: -2 V to +7 V
	Accuracy: $\pm 20$ mV
	Resolution: 16 bits, 250 $\mu$ V
Pull-Up / Pull-Down Current Source / Sink	Range: +24 to -20 mA, programmable on a per channel basis
	Accuracy: $\pm 124$ $\mu$ A
	Resolution: 16 bits
Commutation Voltage (VComm)	Range: -2V to +7V, programmable on a per channel basis Note: VTT and Vcomm share a common voltage source, only one mode supported per channel
	Accuracy (typ): $\pm 20$ mV
	Resolution: 16 bits, 250 $\mu$ V
<b>DIGITAL I/O PARAMETRIC MEASUREMENT UNIT (PMU)</b>	
Number of Parametric Measurement Units	32, one per channel

# GX5296



Configurations	Force Voltage/Measure Current (FVMI) Force Current/Measure Voltage (FIMV) Force Voltage/Measure Voltage (FVMV) Force Current/Measure Current (FIMI)
Force Voltage	Range: -1.5 V to +7 V
	Accuracy: $\pm 20$ mV (max)
	Resolution: 16 bits, 250 $\mu$ V
Force Current	Ranges: $\pm 32$ mA, $\pm 8$ mA, $\pm 2$ mA, $\pm 512$ $\mu$ A, $\pm 128$ $\mu$ A, $\pm 32$ $\mu$ A, $\pm 8$ $\mu$ A, $\pm 2$ $\mu$ A FS
	Accuracy, Test conditions: Vcomm @ 0 volts: $\pm 120$ $\mu$ A, -16 mA to +32 mA, 32 mA range $\pm 40$ $\mu$ A, -6 mA to +8 mA range, 8 mA range $\pm 5$ $\mu$ A, 2 mA range
	Accuracy (typ), Vcomm: +1.75 V to +7 V: $\pm 120$ $\mu$ A, -16 mA to -32 mA $\pm 40$ $\mu$ A, -6 mA to -8 mA
	Resolution: 16 bits
Current Measurement	Accuracy (60 Measurements / Sec), Test conditions: Vcomm @ 0 volts: $\pm 120$ $\mu$ A, -16 mA to +32 mA, 32 mA range $\pm 40$ $\mu$ A, -6 mA to +8 mA range, 8 mA range $\pm 5$ $\mu$ A, 2 mA range $\pm 2.4$ $\mu$ A, 512 $\mu$ A range $\pm 600$ nA, 128 $\mu$ A range $\pm 160$ nA, 32 $\mu$ A range $\pm 80$ nA, 8 $\mu$ A range $\pm 20$ nA, 2 $\mu$ A range
	Accuracy (typ), Vcomm: +1.75 V to +7 V: $\pm 120$ $\mu$ A, -16 mA to -32 mA $\pm 40$ $\mu$ A, -6 mA to -8 mA
	Resolution: 16 bits
	Reading per sec 1 (Aperture 1 Sec)-10,000 (Aperture 0.1 mSec)
Voltage Measurement	Range: -1.5 V to +7 V
	Accuracy : $\pm 2.5$ mV, measurement rate < 50 measurements/sec
	Reading per sec: 1 (Aperture

	1 Sec)-10,000 (Aperture 0.1 mSec)
PMU Commutation Voltage	Range: VCom Lo: -2 V to +5 V, VCom Hi: 0 V to +7 V
	Accuracy: $\pm 50$ mV
	Resolution: 16 bits
Pass / Fail PMU Voltage Comparators	Hi and Lo Voltage Threshold Range: -1.75 V to +7 V Accuracy: $\pm 25$ mV
Pass / Fail PMU Current Comparators	Hi and Lo Current Threshold Range: -32 mA to +32 mA Accuracy @ Vcomm+ 0V: $\pm 200$ $\mu$ A, -16 mA to +32 mA range $\pm 120$ $\mu$ A, -6 mA to +8 mA range $\pm 12$ $\mu$ A, 2 mA range $\pm 4.8$ $\mu$ A, 512 $\mu$ A range $\pm 2.4$ $\mu$ A, 128 $\mu$ A range $\pm 200$ nA, 32 $\mu$ A range $\pm 120$ nA, 8 $\mu$ A range $\pm 80$ nA, 2 $\mu$ A range Accuracy (typ), Vcomm: +1.75 V to +7 V $\pm 200$ $\mu$ A, -16 mA to -32 mA $\pm 120$ $\mu$ A, -6 mA to -8 mA
<b>AUXILIARY I/O PARAMETRIC MEASUREMENT UNIT (PMU)</b>	
Number of Parametric Measurement Units	4, one per auxiliary channel
Configurations	Force Voltage/Measure Current (FVMI) Force Current/Measure Voltage (FIMV) Force Voltage/Measure Voltage (FVMV) Force Current/Measure Current (FIMI)
Force Voltage	Range: -1.5 V to +7 V
	Accuracy: $\pm 20$ mV (max)
	Resolution: 16 bits, 250 $\mu$ V
Force Current	Ranges : $\pm 32$ mA, $\pm 8$ mA, $\pm 2$ mA FS
	Accuracy, Test conditions: Vcomm @ 0 volts: $\pm 120$ $\mu$ A, -16 mA to +32 mA, 32 mA range $\pm 40$ $\mu$ A, -6 mA to +8 mA range, 8 mA range $\pm 5$ $\mu$ A, 2 mA range
	Accuracy (typ), Vcomm: +1.75 V to +7 V: $\pm 120$ $\mu$ A, -16 mA to -32 mA $\pm 40$ $\mu$ A, -6 mA to -8 mA

DIGITAL I/O



# GX5296



	Resolution: 16 bits
Current Measurement	Accuracy (60 Measurements / Sec), Test conditions: Vcomm @ 0 volts: ±120 uA, -16 mA to +32 mA, 32 mA range ±40 uA, -6 mA to +8 mA range, 8 mA range ±5uA, 2 mA range
	Accuracy (typ), Vcomm: +1.75 V to +7 V: ±120 uA, -16 mA to -32 mA ±40 uA, -6 mA to -8 mA
	Resolution: 16 bits
	Reading per sec 1 (Aperture 1 Sec)-10,000 (Aperture 0.1 mSec)
Voltage Measurement	Range: -1.5 V to +7 V
	Accuracy: ±3.0 mV (measurement rate < 50 measurements / sec)
	Reading per sec: 1 (Aperture 1 Sec)-10,000 (Aperture 0.1 mSec)
PMU Commutation Voltage	Range: VCom Lo: -2 V to +5 V, VCom Hi: 0 V to +7 V
	Accuracy: ±50 mV
	Resolution: 16 bits
Pass / Fail PMU Voltage Comparators	Hi and Lo Voltage Threshold Range: -1.75 V to +7 V Accuracy: ±25 mV
Pass / Fail PMU Current Comparators	Hi and Lo Current Threshold Range: -32 mA V to +32 mA Accuracy @ Vcomm= 0V: ±200 uA, -16 mA to +32 mA range ±120 uA, -6 mA to +8 mA range ±12 uA, 2 mA range Accuracy (typ), @Vcomm= +1.75 V to +7 V: ±200 uA, -16 mA to -32 mA ±120 uA, -6 mA to -8 mA
<b>POWER (IDLE AND INITIALIZED)</b>	
+3.3 VDC	4.8 A
+5 VDC	1.48 A
+12 VDC	0.25 A
<b>ENVIRONMENTAL</b>	
Operating Temperature	0 °C to +50 °C
Storage Temperature	-20 °C to +70 °C
Size	3U PXI

Weight	200 g
<b>FRONT PANEL CONNECTORS</b>	
J1	Digital I/O Signals, 68-pin VHD connector
J3	Timing & Control Signals, 68-pin VHD connector
<b>CALIBRATION</b>	
Calibration Interval	1 year

Note: Specifications are subject to change without notice

## ORDERING INFORMATION

GX5296	Dynamic Digital I/O (3U), 32 ch., per pin voltage & direction control; 125 MHz w/64 M Vectors per channel; per pin timing & PMU
<b>SOFTWARE</b>	
GtDio6x-FIT	Digital File Import Tool Option for GX5296 DIO
GtDio6x-FIT-S1Y	Renew GtDio6x-FIT Subscription and Support 1 Year (requires continuous agreement)
GtDio6x-FIT-S2Y	Renew GtDio6x-FIT Subscription and Support 2 Years (requires continuous agreement)
GtDio6x-FIT-S3Y	Renew GtDio6x-FIT Subscription and Support 3 Years (requires continuous agreement)
GtDio6x-FIT-EXP6	1-year Renewal Expired GtDio6x-FIT Subscription and Support (expired 1 day to 6 months)
GtDio6x-FIT-EXP24	1-year Renewal Expired GtDio6x-FIT Subscription and Support (expired 7 to 24 months)
GtDio6x-FIT-SUP	1-year Support only for GtDio6x-FIT (no upgrades)
<b>ACCESSORY</b>	
TS-900e-56-BMC	Blind mate connectors (one pair), DC - 40 GHz, 2.92mm
GT95021	2 ft. Shielded Cable for all 5xxx/35xx (68 Pin)
GT95022	3 ft Shielded Cable for all 5xxx/35xx (68 Pin)
GT95022E	3 ft Shielded Cable for all 5xxx/35xx (68 Pin) Not Terminated One End
GT95025	Connector Interface, 68-Pin SCSI to TTI Testron 170-Pin Signal Block
GT95028	10 ft shielded cable for 5xxx/35xx products (68 Pin)
GT95031	6 ft Shielded Cable for all 5xxx/35xx (68 Pin)
GT95035E-48	Shielded Flying Lead Cable for all 5xxx/35xx (68 Pin), 48".
GT95015	Connector Interface for all Gx5xxx/GX3xxx, SCSI to 100 Mil Grid, Differential
<b>CALIBRATION</b>	
GX5295-96-CALKIT	Calibration cable kit for use with the GX5295 / GX5296 DIO modules & CalEasy



# GX5296



<b>CalEasy-GX5296</b>	CalEasy for the GX5296 (Single User License) with One Year Support and Subscription
<b>CalEasy</b>	CalEasy License for all Supported Marvin Test Solutions Products (Single User License) with One Year Support and Subscription
<b>CalEasy-2Y</b>	CalEasy License for all Supported Marvin Test Solutions Products (Single User License) with Two Year Support and Subscription
<b>CalEasy-3Y</b>	CalEasy License for all Supported Marvin Test Solutions Products (Single User License) with Three Year Support and Subscription
<b>GT95015-CAL</b>	Connector Interface board with capacitors, for calibrating GX5295/ GX5295
<b>GX5296-CAL</b>	GX5296 Calibration/Verification Service. Includes pre-verification data (post calibration data provided if applicable)
<b>GX5296-CAL-3</b>	GX5296 Calibration/Verification Service - 3 Years. Includes pre-verification data (post calibration data provided if applicable)
<b>GX5296-CAL-5</b>	GX5296 Calibration/Verification Service - 5 Years. Includes pre-verification data (post calibration data provided if applicable)

# GX5296



THIS PAGE INTENTIONALLY LEFT BLANK

